


TP6


CUTTING AND BENDING MACHINE FOR AXIAL COMPONENTS



20.OL01 STANDARD LEAD Ø: 0,4 -1,2

20.OL04 REINFORCED LEAD Ø: 0,6 – 1,4

20.OL06 REDUCED LEAD Ø: 0,4 – 0,8



20.OL07/9/10 REDUCED AND FIX PITCH LEAD Ø: 0,4 – 0,6

20.OL0130 STRAIGHT CUT



The model TP6 is designed for cutting and bending taped axial components with lead diameter from 0,4 to 1,4mm (.015 to .055"). The high quality and reliability of this machine ensure the best operation for a very long time. No maintenance is required.




PRODUCTION/HOUR
TAPED: 50000
LOOSE: 5000

STANDARD VERSIONS OF TP6, TP6/D AND TP6/97 MACHINES

20.OL01 - 20.OL11 - 20.OL01/97


TP6/1 STANDARD VERSION



	MM		IN	
	min	max	min	max
P	6,5	60	.255	2.362
B	4	13	.157	.511
c	1,2		.047	
L		50		1.968
d	0,4	1,2	.015	.047
D	0,4	16	.015	.629

20.OL04 - 20.OL12 - 20.OL04/97


TP6/4 EXTRA REINFORCED BENDING



	MM		IN	
	min	max	min	max
P	10,16	60	.4	2.362
B	5	13	.196	.511
c	2,4		.094	
L		50		1.968
d	0,6	1,4	.023	.055
D	0,6	16	.023	.629

20.OL06 - 20.OL06/97


TP6/6 REDUCED BENDING – ADJUSTABLE PITCH



	MM		IN	
	min	max	min	max
P	5,08	60	.2	2.362
B	4	13	.157	.511
c	0,8		.031	
L		50		1.968
d	0,4	0,8	.015	.031
D	0,4	10	.015	.039

20.OL07 - 20.OL09 - 20.OL10

TP6/7 – TP6/9 – TP6/10 REDUCED BENDING FIX PITCH



	MM		IN	
	min	max	min	max
B	4	10	.157	.393
c	0,5		.019	
d	0,4	0,6	.015	.023
D	0,4	4	.015	.157
code 20.OL07	P	5,08	.2	
code 20.OL09	P	7,62	.3	
code 20.OL10	P	10,16	.4	


TP6 OPTIONAL ACCESSORIES




BR6 - 400200 REEL HOLDER




MOT98 - 7915030 - 220 V. -MOTOR DRIVE UNIT
MOT98 - 7915031 - 110 V - MOTOR DRIVE UNIT.



TNS - 21.0011 WASTE TAPE EJECTOR



CS10 - 51.0100 FEEDER FOR LOOSE COMPONENTS



200240 BODY GUIDE

MAX LEGHT COMPONENT BODY = 45 MM
