



TP6-EC

CUTTING AND BENDING MACHINE FOR AXIAL COMPONENTS



23.OL01 STANDARD LEAD: 0,4 -1,3



23.OL04 REINFORCED LEAD: 0,6 -1,4



23.OL06 REDUCED LEAD: 0,4 -0,8

23.OL07/09/10 REDUCED AND FIX PITCH LEAD Ø: 0,4 - 0,6

23.OL0130 STRAIGHT CUT


The model TP6-EC is a manual machine, designed for cutting and bending taped axial components with lead diameter from 0,4 to 1,2 mm (.015 to .047"). Operation quota are set up in a quick and precise manner. The high quality and reliability of this machine ensure the best operation for a very long time. No maintenance is required. This machine is only supplied manual version and

PRODUCTION: 50000/HOUR




TP6/1-EC
STANDARD - 23.OL01

	MM		IN	
	min	max	min	max
P	6,5	60	.255	2.362
B	4	13	.157	.511
c	1,2		.047	
L		50		1.968
d	0,4	1,2	.015	.047
D	0,4	16	.015	.629




TP6/4-EC
REINFORCED - 23.OL04

	MM		IN	
	min	max	min	max
P	10,16	60	.4	2.362
B	5	13	.196	.511
c	2,4		.094	
L		50		1.968
d	0,6	1,4	.023	.055
D	0,6	16	.023	.629




TP6/6-EC
REDUCED - 23.OL06

	MM		IN	
	min	max	min	max
P	5,08	60	.2	2.362
B	4	13	.157	.511
c	0,8		.031	
L		50		1.968
d	0,4	0,8	.015	.031
D	0,4	10	.015	.039



TP6/7-EC
REDUCED FIX PITCH - 23.OL07



	MM		IN	
	min	max	min	max
B	4	10	.157	.393
c	0,5		.019	
d	0,4	0,6	.015	.023
D	0,4	4	.015	.157

code 23.OL07	P	5,08	.2
code 23.OL09	P	7,62	.3
code 23.OL10	P	10,16	.4